



Hot Coils® Specifications

Std. Pipe Dia. Model No.	4 400	6 600	8 800	10 1000	12 1200
Voltage	110 / 120	110 / 120	110 / 120	110 / 120	110 / 120
Hertz	60 Cycle	60 Cycle	60 Cycle	60 Cycle	60 Cycle
Watts	1500	1500	1500	1500	1500
Amp.	15	15	15	15	15
Max. Inside Temp. (1)	550°F (286°C)	550°F (286°C)	550°F (286°C)	550°F (286°C)	550°F (286°C)
Time to Max. Temp (1)	20 min.	20 min.	20 min.	20 min.	20 min.
Adjustable Thermostat	Standard	Standard	Standard	Standard	Standard
Thermostat Accuracy	+/- 2.5 F	+/- 2.5 F	+/- 2.5 F	+/- 2.5 F	+/- 2.5 F
Coil Wall Thickness	1.75" (45 mm)	1.75" (45 mm)	1.75" (45 mm)	1.75" (45 mm)	1.75" (45 mm)
Outside Dia.	7.5" (191 mm)	9.5" (241 mm)	11.5" (292 mm)	13.5" (343 mm)	15.5" (394 mm)
Width	6 in. (150 mm)	6 in. (150 mm)	6 in. (150 mm)	6 in. (150 mm)	6 in. (150 mm)
Weight	6lbs (2.7 kg)	6.5lbs (2.9 kg)	7lbs (3.2 kg)	7.5lbs (3.4 kg)	8lbs (3.6 kg)

(1) Based on 4 inch schedule 40 pipe at an ambient temperature of 70° F (21° C)